

**AMENDMENTS TO THE CLAIMS:**

Please replace the claims with the claims provided in the listing below wherein status, amendments, additions and cancellations are indicated.

1. (Currently Amended) A method for analyzing a ground structure, said method comprising:

positioning ~~three~~ a plurality of microseismic oscillation wave sensors for defining a substantially equilateral triangular configuration and so that there is a sensor at each of at least 3 measurement points within an area at ground level[.]);

~~for simultaneously measuring~~ microseismic oscillations at said measurement points to obtain data generated by said microseismic oscillations, said data including horizontal oscillation data and/or vertical oscillation data;

changing the locations of said measurement points;

repeating the measurements; ~~and~~

analyzing the obtained oscillation data; and

determining a direction of origin of the microseismic oscillations from the measured oscillation data.

2. (Previously Presented) The method according to claim 1, wherein said microseismic oscillations to be measured are short-period microseisms observed at ground level.

F7917 em 03 (PC14) wpd

Docket No. F-7917

Ser. No. 10/634,539

3. (Previously Presented) The method according to claim 1, wherein two sensors are disposed on each of at least two straight lines passing through the ground to be measured, and a 360 degree azimuth is divided into an even-number of equal sections or straight lines parallel thereto such that sensor-to-sensor distances are equal on said straight lines.

4. (Previously Presented) The method according to claim 1, wherein said sensors are positioned at least a total of four points, including at least three points at equal spacings on a circumference of a circle, and at one point at a geometric center of the circle.

5. (Previously Presented) The method according to claim 1, wherein said sensors are positioned at least a total of four points, including at apices of a regular triangle, and at a geometric center of said triangle.

6. (Previously Presented) The method according to any of claims 1 to 5, further comprising:

analyzing one of vertical oscillation data and both vertical and horizontal oscillation data, as measured simultaneously with said sensors;

determining whether the microseismic oscillations detected by said sensors are, or are not, surface waves; and

Docket No. F-7917

Ser. No. 10/634,539

extracting and analyzing the surface waves.

7. (Currently Amended) The method according to any of claims 1 to 5-6, further comprising:

analyzing a correlation coefficient and phase difference of oscillation data, as measured by equally spaced sensors for each;

performing repeated analyses at varying sensor-to-sensor distances;

analyzing and computing a fundamental mode of surface waves, based on results of the respective analyses; and

analyzing and computing higher-mode wave-lengths.

8. (Currently Amended) The method according to any of claims 1 to 5-7, further comprising repeatedly performing measurement and analysis of said microseismic oscillations until existence of a relation between phase velocity and wavelength is alternatively established or refuted, such that when a relation is established therebetween, an inference of an accurate assessment of ground structure can be made.